



Prostal Limited.

1F., No.40, Aly. 22, Ln. 143, Ruiping Rd., Yangmei Disty, Taoyuan City 32658, Taiwan

TEL: +886-3-4828372 Fax: +886-3-4828377

URL: www.prostal.com.tw E-MAIL: joan@prostal.com.tw

Vat number: 24849130

YW-H620 Optical power meter

Advantages

- Long useful life of Battery
- Self-calibrating function
- Prompt response
- Large LCD display, multi functions
- 2.5mm universal adapter to avoid complex conversion
- Auto switch off function (optional)



General

YW-H620 handheld optical power meter is one of Prostal's newly developed multi-functional power meter with large LCD display, auto switch off function. It features accurate test, durable, portable design test instruments designed for the installation, construction and maintenance of optical fiber network.

Specifications

Type	YW-H620A	YW-H620C
Wavelength range (nm)	800~1700	
Detector	InGaAs	
Measurement range (dBm)	-70~+6	-50~+26
Uncertainty	±5%	
Calibrated Wavelength (nm)	850、980、1310、1490、1550 (can be specified)	
Display Resolution	0.1% & 0.01dBm	
Operating temperature (°C)	-10~+60	
Storage temperature (°C)	-25~+70	
Auto-off time (min)	10	
Battery working hours (h)	240	
Dimension (mm)	148×74×28	
Power Supply	Alkaline battery (3 AA 1.5V battery)	
Weight (g)	225	