



Prostal Limited.

1F., No.40, Aly. 22, Ln. 143, Ruiping Rd., Yangmei Disty, Taoyuan City 32658, Taiwan

TEL: +886-3-4828372 Fax: +886-3-4828377

URL: www.prostal.com.tw E-MAIL: joan@prostal.com.tw

Vat number: 24849130

YW-H430 Optical light source

Advantages

- More wavelength output (maximum can be 4 wavelength)
- CW output or modulation output
- 45 hours continuous working time
- Large LCD display
- Easy operation with one key to change wavelength
- 10 minutes optional auto switch off function



General

YW-H430 adopted the outstanding technique of same type of products; it can provide 1 to 4 wavelength output according to the specific requirements.

Specifications

Type	YW-H430
Wavelength (nm)	More wavelength can be optional ,maximum can be four wavelength
Emitter Type	FP-LD
Output Power(dBm)	0 (at 650nm is 0 dBm) /-7/-7
Modulation Frequencies	CW / 2Hz (650) / 270Hz,1KHz,2KHz (1310, 1550)
Fiber Type	SM , MM
Optical Interface	FC/PC (Universal adapter)
Power supply	Alkaline battery (3 AAA 1.5V battery)
Operating temperature (°C)	-10~+60
Storage temperature (°C)	-25~+70
Battery working hours (h)	45
Dimension (mm)	148×74×28
Weight (g)	225