



Prostal Limited.

1F., No.40, Aly. 22, Ln. 143, Ruiping Rd., Yangmei Disty, Taoyuan City 32658, Taiwan

TEL: +886-3-4828372 Fax: +886-3-4828377

URL: www.prostal.com.tw E-MAIL: joan@prostal.com.tw

Vat number: 24849130

LC adaptors with auto shutter

To protect people from dangerous Laser, Prostal design and supply fiber optics adaptors with auto shutter. LC adaptors with auto shutter use SC adaptor foot print.



Features:

- ❖ Auto shutter options: external auto shutter door and internal auto shutter metal plate
- ❖ Option to with flanges or without flange
- ❖ Diversity: Many colors are available, include: blue, green, black, aqua, beige, and magenta.
- ❖ High reliability: the assembly is done in factory, 100% tests before shipment.
- ❖ Complies with GR-326-CORE and RoHS.

Performance specifications:

Sleeve material:	Ceramic
Typical Insertion Loss:	0.1dB
Maximum Insertion Loss:	0.3dB
Operating temperature:	-40~75°C
Storage Temperature:	-55~85°C

Ordering Information

ASLCA - <input type="text"/>	- <input type="text"/>	- <input type="text"/>
Types of shutter door: F = Front plastic type M = Internal metal plate type	Number of port: 2 = 2 ports 4 = 4 ports	Color: B = Blue G = Green B = Beige