



## Prostal Limited.

Vat number: 24849130

1F., No.40, Aly. 22, Ln. 143, Ruiping Rd., Yangmei Disty, Taoyuan City 32658, Taiwan

TEL: +886-3-4828372 Fax: +886-3-4828377

URL: [www.prostal.com.tw](http://www.prostal.com.tw) E-MAIL: [joan@prostal.com.tw](mailto:joan@prostal.com.tw)

## MU connector

Prostal Limited, a legal supplier for MU connector, MU adapter, MU attenuator, etc.

Our MU uniboot connectors is for 3.0mm diameter single cable with two fiber inside. It can decrease the amount of cables in half and also are suitable for data centers. It have push and pull function to make install process easier, safer and quicker.

**MU Uniboot Connector**



**MU Push-Pull Tab**



The above picture shows Mu Uniboot Connector with Push-Pull Tab working on the 36C MPO module



## Prostal Limited.

Vat number: 24849130

1F., No.40, Aly. 22, Ln. 143, Ruiping Rd., Yangmei Disty, Taoyuan City 32658, Taiwan

TEL: +886-3-4828372 Fax: +886-3-4828377

URL: [www.prostal.com.tw](http://www.prostal.com.tw) E-MAIL: [joan@prostal.com.tw](mailto:joan@prostal.com.tw)

We supply standard MU connector as well. It works with 0.9mm, 2.0mm, 3.0mm round cables.

MU connector for 0.9mm/2.0mm/3.0mm cables



### Features:

- ✧ Low insertion loss
- ✧ Low back reflection loss
- ✧ Easy to handle
- ✧ Customer defined specifications
- ✧ Environmentally stable

### Performance specifications:

Typical Insertion Loss:	0.15dB (singlemode), 0.3dB (multimode)
Typical Return Loss:	-50dB (singlemode)
Operating temperature:	-40~75°C
Storage Temperature:	-55~85°C