



Prostal Limited.

1F., No.40, Aly. 22, Ln. 143, Ruiping Rd., Yangmei Disty, Taoyuan City 32658, Taiwan

TEL: +886-3-4828372 Fax: +886-3-4828377

URL: www.prostal.com.tw E-MAIL: joan@prostal.com.tw

Vat number: 24849130

YW-H440i Optical Stable Light Source

Advantages

- Large LCD display
- Battery low voltage detecting and displaying
- High stability of output power
- Easy operation with one key to change wavelength
- High stability of output power
- Output power mode CW can be optional
- Unique FC/SC/ST universal adapter, easy for clean



General

YW-H440i Handheld Optical Stable Light Source is our newly Developed test instrument, together with YW-H640i Optical Power Meter, It can provide accurate solution for optical network.

Specification

Type	YW-H440i
Wavelength	One to four wavelength can be optional
Emitter Type	FP-LD or other can be specified
Output Power (dBm)	0dBm(650nm)/-7/-7dBm
Output Modulation	CW / 2Hz (650) / 270Hz, 1KHz, 2KHz (1310, 1550)
Fiber Type	Single mode or Multi mode
Output Connector	FC/SC/ST
Power Supply	4 AA, AC adapter 9V
Operating Temperature (°C)	-10~+60
Storage Temperature (°C)	-25~+70
Dimension (mm)	180×80×48
Unit Weight (g)	360